

Restic : Ligne de commandes

Bashrc & Alias

Sur votre utilisateur courant (différent de root), éditer votre fichier bashrc `vim /home/user/.bashrc`

```
alias restic='restic --insecure-tls'
export RESTIC_PASSWORD="${USER_MDP}"
export
RESTIC_REPOSITORY="rest:https://${USER_PROJECT}:${USER_MDP}@${SRV_RESTIC}:${PORT_EXPOSED}/"
```

Cela permet ensuite d'utiliser le binaire vers votre dépôt de sauvegarde sans à divulguer toutes les informations :

```
zayad@vmi2007645:~$ restic stats
repository 6d0ed1e0 opened (repository version 2) successfully, password is correct
scanning...
Stats in restore-size mode:
Snapshots processed:    2
  Total File Count:    281
    Total Size:       24.191 KiB
```

Backing Up

```
restic backup ~/directory-to-backup --pack-size=60
```

Cleanup

With every backup, Restic is creating a new snapshot with contents of a directory at the moment. To remove old and unused snapshots we need to execute the forget command:

```
restic forget --keep-last 2 --prune
```

Check

If you want to verify the consistency of your backup, run the check command:

```
restic check
```

Restore

To restore the latest snapshot of your backup:

```
restic restore latest --target ~/restore
```

Revision #8

Created 2024-07-22 01:31:03 UTC by Zayad

Updated 2024-07-23 04:40:18 UTC by Zayad